



-18°C ÷ +80°C



Working pressure:
12 Bar



Compressed air



- Taper gas BSPT ISO 7
R3/8" and R1/2"
- Parallel gas BSPP ISO 228
G3/8" and G1/2"



Body: Nickel-plated brass
Spring: Nickel-plated steel

PROFILE - LARGE SERIES



NOMINAL DIAMETER

9,2 mm

AIR FLOWRATE

2500 l/min



Products in compliance with
EC Regulation 1907/2006



Products in compliance with
the directive EU 2015/863

VIEW - QUICK COUPLING 8215FM



8215FM

Large male quick coupling BSPT thread



| CODE | THREAD | LENGTH | WRENCH |
|----------|--------|--------|--------|
| 8215FM03 | R 3/8" | 62,5 | 26 |
| 8215FM04 | R 1/2" | 65,0 | 26 |

8225FF

Large female quick coupling BSPP thread



| CODE | THREAD | LENGTH | WRENCH |
|----------|--------|--------|--------|
| 8225FF03 | G 3/8" | 62,0 | 26 |
| 8225FF04 | G 1/2" | 65,0 | 26 |

8235PO

Large quick coupling with hose connector



| CODE | Ø | LENGTH | WRENCH 1 | WRENCH 2 |
|------------|-------|--------|----------|----------|
| 8235PO1019 | 10x19 | 96,0 | 26 | 24 |
| 8235PO1020 | 10x20 | 96,0 | 26 | 25 |
| 8235PO1021 | 10x21 | 96,0 | 26 | 25 |
| 8235PO1022 | 10x22 | 96,5 | 26 | 26 |
| 8235PO1023 | 10x23 | 96,5 | 26 | 27 |
| 8235PO1319 | 13x19 | 97,5 | 26 | 24 |
| 8235PO1320 | 13x20 | 97,5 | 26 | 25 |
| 8235PO1321 | 13x21 | 97,5 | 26 | 25 |
| 8235PO1323 | 13x23 | 98,0 | 26 | 27 |
| 8235PO1324 | 13x24 | 97,5 | 26 | 30 |
| 8235PO1325 | 13x25 | 97,5 | 26 | 30 |



8245PO

Large connection with hose connector



| CODE | Ø | LENGTH | WRENCH 1 | WRENCH 2 |
|------------|-------|--------|----------|----------|
| 8245PO1019 | 10x19 | 95,0 | 26 | 25 |
| 8245PO1020 | 10x20 | 95,5 | 26 | 25 |
| 8245PO1021 | 10x21 | 96,0 | 26 | 25 |
| 8245PO1022 | 10x22 | 96,0 | 26 | 25 |
| 8245PO1023 | 10x23 | 96,0 | 26 | 27 |
| 8245PO1319 | 13x19 | 97,5 | 26 | 25 |
| 8245PO1320 | 13x20 | 97,5 | 26 | 25 |
| 8245PO1321 | 13x21 | 97,5 | 26 | 25 |
| 8245PO1323 | 13x23 | 97,5 | 26 | 27 |
| 8245PO1324 | 13x24 | 97,5 | 26 | 27 |
| 8245PO1325 | 13x25 | 97,5 | 26 | 30 |

8255MM

Large male connection BSPT thread



| CODE | THREAD | LENGTH | WRENCH |
|----------|--------|--------|--------|
| 8255MM03 | R 3/8" | 47,5 | 19 |
| 8255MM04 | R 1/2" | 50,5 | 22 |

