

-20°C ÷ +110°C subject to applications



Up to 14 Bar at 20°C



Compressed air, water and food fluids suitable with construction materials



Taper gas BSPT ISO 7 from R1/8" to R3/4" NPT from N1/8" to N3/4"



Nylon 66

PRECAUTIONS

- The products are made in plastic and it's necessary to use teflon coating over the thread for installation in order and to prevent air leakage. Be sure to prevent excessive torque when screwing the fittings.
- To connect the tube, insert the tube to the end and tight the cap before use.
- Cut the pressed part of the tube before connection to reuse the released tube.



Products in compliance with the directive 2002/95/EC

RECOMMENDED TIGHTENING TORQUE

THREAD SIZE	NM	FT LB
1/8	0,1	0,07
1/4	0,8	0,6
3/8	4	3
1/2	6	4
3/4	8	6
1	10	7


RoHS2

Products in compliance with the directive 2011/65/EU



1800


Nipple BSPT thread



CODE	T	L	I	H	GR.
1800TR18	R1/8"	23,0	8,0	14	1,4
1800TR14	R1/4"	27,0	10,0	17	3,5
1800TR38	R3/8"	28,0	10,0	19	4,2
1800TR12	R1/2"	34,0	12,5	22	8,0

1802

Reduced nipple BSPT thread



CODE	T1	T2	I1	I2	L	H	GR.
1802TR1418	R1/4"	R1/8"	10,5	8,5	25,0	17	2,5
1802TR3818	R3/8"	R1/8"	10,0	8,0	26,0	19	3,8
1802TR3814	R3/8"	R1/4"	10,0	10,0	28,0	19	4,1
1802TR1214	R1/2"	R1/4"	13,0	10,5	31,5	22	6,7
1802TR1238	R1/2"	R3/8"	13,0	10,5	31,5	22	6,0

