

20°C ÷ +120°C
subject to applications



Up to 14 Bar at 20°C



Compressed air, water and food fluids suitable with construction materials



Taper gas BSPT ISO 7 from R1/8" to R3/4"



Polyvinylidene fluoride (PVDF)

FEATURES

To be used with all kind of very corrosive fluids like acids, weak bases, halogens, alcohols, salts, heavy duty oxidants, detergents, ecc. Uv resistant, Nuclear resistant.

Available on demand with NPT thread



Products in compliance with the directive 2002/95/EC

RoHS2

Products in compliance with the directive 2011/65/EU




RECOMMENDED TIGHTENING TORQUE

THREAD SIZE	NM	FT LB
1/8	0,1	0,07
1/4	1	0,8
3/8	5	3
1/2	8	6
3/4	16	12
1	26	19

1900


Nipple BSPT thread



CODE	T	L	I	H	GR.
1900TR18	R1/8"	23,0	8,0	14	1,4
1900TR14	R1/4"	27,0	10,0	17	3,5
1900TR38	R3/8"	28,0	10,0	19	4,2
1900TR12	R1/2"	34,0	12,5	22	8,0

1902

Reduced nipple BSPT thread



CODE	T1	T2	I1	I2	L	H	GR.
1902TR1418	R1/4"	R1/8"	10,5	8,5	25,0	17	2,5
1902TR3818	R3/8"	R1/8"	10,0	8,0	26,0	19	3,8
1902TR3814	R3/8"	R1/4"	10,0	10,0	28,0	19	4,1
1902TR1218	R1/2"	R1/8"	13,0	12,0	35,0	22	6,1
1902TR1214	R1/2"	R1/4"	13,0	10,5	31,5	22	6,7
1902TR1238	R1/2"	R3/8"	13,0	10,5	31,5	22	6,0

