

R-PTFE-PROF

Teflon tape for professional use



CODE	DESCRIPTION	THICKNESS	CONTAINER
R-PTFE190215-PROF	For professional use according to directive DIN - DVGW, BS 7786 and GASTEC norms and to use in a temperature range from -200°C to +260°C.	0,2 MM	15 MT.

2605

Metal seal



CODE	THREADS	D	THICKNESS	GR.
2605TR18	1/8"	14	1	10
2605TR14	1/4"	17	1	20
2605TR38	3/8"	22	1,3	10
2605TR12	1/2"	26	1,6	20
2605TR34	3/4"	32	1,6	22
2605TR1	1"	39	3,5	28

2610

Nylon notched washer



CODE	THREADS	A	B	C	GR.
2610TRM5	M5	8,0	5,2	1,3	2,0
2610TR18	G1/8"	14,0	10,0	2,0	26,0
2610TR14	G1/4"	18,0	13,5	2,0	42,0
2610TR38	G3/8"	21,0	16,8	2,0	28,0
2610TR12	G1/2"	26,0	21,1	2,0	38,0

2612

PVC washer



CODE	THREADS	D4	D4	H	GR.
2612TR18	G1/8"	14,0	10,0	1,5	18,0
2612TR14	G1/4"	17,5	13,5	1,5	18,0
2612TR38	G3/8"	21,0	16,7	1,5	18,0
2612TR12	G1/2"	26,0	21,3	1,5	18,0

