

## 20AC111

Connector with barb connection



CODE	VALVED	ØD	L	H
20AC111L-48	NO	4,8	24,6	14,0
20AC111V-48	YES	4,8	41,9	14,0
20AC111L-63	NO	6,3	28,4	14,0
20AC111V-63	YES	6,3	45,7	14,0
20AC111L-76	NO	7,6	28,4	14,0
20AC111V-76	YES	7,6	45,7	14,0

## 40AC111

Connector with barb connection



CODE	VALUED	ØD	L	H
40AC111L-76	NO	7,6	31,8	17,8
40AC111V-76	SI	7,6	49,3	17,8
40AC111L-91	NO	9,1	31,8	17,8
40AC111V-91	SI	9,1	49,3	17,8
40AC111L-107	NO	10,7	31,8	17,8
40AC111V-107	SI	10,7	46,5	17,8

## 20AC121

Bulkhead connector with barb connection



CODE	VALVED	ØD	L	H
20AC121L-48	NO	4,8	41,1	15,7
20AC121V-48	SI	4,8	41,1	15,7
20AC121L-63	NO	6,3	44,7	15,7
20AC121V-63	SI	6,3	44,7	15,7
20AC121L-76	NO	7,6	44,7	15,7
20AC121V-76	SI	7,6	44,7	15,7

## 40AC121

Bulkhead connector with barb connection



CODE	VALUED	ØD	L	H
40AC121L-76	NO	7,6	47,8	19,1
40AC121V-76	SI	7,6	47,8	19,1
40AC121L-91	NO	9,1	47,8	19,1
40AC121V-91	SI	9,1	47,8	19,1
40AC121L-107	NO	10,7	47,8	19,1
40AC121V-107	SI	10,7	47,8	19,1

